HYT RC



COMPACT ELECTRIC PUMP

This compact pump is well suited for the wind energy sector due to its relatively low weight and small size. The pump is mounted in a durable steel frame with rubber feet and comes complete with a hydraulic quick connect fitting.

NOTES

- The two stage pump is factory set to provide high volume oil flow to the tensioner.
- The pump automatically switches to high pressure mode ensuring the desired operating pressure is achieved quickly.
- To increase efficiency and reduce maintenance the pump is fitted with a lightweight brushless motor which allows the pump to operate at a low noise level.

SPECIFICATION		1500 BAR PUMP	2500 BAR PUMP
Maximum Output Pressure		1500 bar (21,750 psi)	2500 bar (36,250 psi)
Maximum Pressure Valve		Manually Adjustable Pressure Relief Valve	e Manually Adjustable Pressure Relief Valve
Power Rating		0.75kW	075kW
Weight	Without	71.7 lbs (32.5 kg)	71.7 lbs (32.5 kg)
			82.7 lbs (37.5 kg)
	Oil	1.3 gal (5 l)	1.3 gal (5 l)
Hydraulic Oil Capacity			
Recommended Hydraulic Oil		ISO-32 or ISO-46	ISO-32 or ISO-46
Pump Capacity		1st Stage: 3.5 /min up to 1500 bar (psi) 2nd Stage: 0.4 /per min up to 1500 bar (21 psi)* *at 50Hz (at 60Hz +20%)	, , ,
Electric Motor Options		200V-240V, 50/60Hz Single Phase 110V-120V, 50/60Hz Single Phase 240V, 50/60Hz 3 Phase 400V, 50/60Hz Single Phase Protection Rating: IP54	200V-240V, 50/60Hz Single Phase 110V-120V, 50/60Hz Single Phase 240V, 50/60Hz 3 Phase 400V, 50/60Hz Single Phase Protection Rating:

The World's Most Trusted Industrial Bolting Systems

HYTORC owns all content, copyrights, trademarks and patents in this document. © 2021 HYTORC. Any unauthorized use or distribution of any material from this document is strictly prohibited.



Address:

PH Ofidepositos Tocumen, Bodega #10 Via Panamericana, Mañanitas. Ciudad de Panamá, Panamá

Phone: 507 382-8015

Emaii:

info@toolsolutionscorp.com

Online:

toolsolutionscorp.com